

Hose Clamp Size Chart: SAE Sizes by Maker

Worm-drive clamp ranges in inches, as each maker prints them. Pick the size whose range is just larger than the hose.

SAE SIZE	BREEZE POWER-SEAL (1/2" BAND)	MURRAY GOLD SEAL H (1/2" BAND)	BREEZE MINI (5/16" BAND)
4	n/a	n/a	7/32" to 5/8"
6	7/16" to 25/32"	7/16" to 25/32"	7/16" to 25/32"
8	1/2" to 29/32"	7/16" to 29/32"	1/2" to 29/32"
10	9/16" to 1-1/16"	9/16" to 1-1/16"	9/16" to 1-1/16"
12	11/16" to 1-1/4"	11/16" to 1-1/4"	11/16" to 1-1/4"
16	13/16" to 1-1/2"	3/4" to 1-1/2"	15/16" to 1-1/2"
20	13/16" to 1-3/4"	13/16" to 1-3/4"	1-3/16" to 1-3/4"
24	1-1/16" to 2"	1-1/16" to 2"	1-7/16" to 2"
28	1-5/16" to 2-1/4"	1-5/16" to 2-1/4"	1-11/16" to 2-1/4"
32	1-9/16" to 2-1/2"	1-9/16" to 2-1/2"	1-15/16" to 2-1/2"
36	1-13/16" to 2-3/4"	1-13/16" to 2-3/4"	n/a
40	2-1/16" to 3"	2-1/16" to 3"	n/a
44	2-5/16" to 3-1/4"	2-5/16" to 3-1/4"	n/a
48	2-9/16" to 3-1/2"	2-9/16" to 3-1/2"	n/a
52	2-13/16" to 3-3/4"	2-13/16" to 3-3/4"	n/a
56	3-1/16" to 4"	3-1/16" to 4"	n/a
60	3-5/16" to 4-1/4"	3-5/16" to 4-1/4"	n/a
64	3-9/16" to 4-1/2"	3-9/16" to 4-1/2"	n/a
72	1-7/8" to 5"	4-1/16" to 5"	n/a
80	2-1/2" to 5-1/2"	4-9/16" to 5-1/2"	n/a
88	3-1/8" to 6"	5-1/16" to 6"	n/a
96	3-5/8" to 6-1/2"	5-9/16" to 6-1/2"	n/a
104	4-1/8" to 7"	6-1/16" to 7"	n/a

Measure the hose's outside diameter while it's on its fitting, in three places, and average them (Murray).

Choose the range just slightly larger than the hose, and no bigger than you need (Murray).

Breeze Power-Seal and Murray Gold Seal H share the same maximum in every row. Some minimums differ.

Breeze Mini has a 5/16" band and stops at SAE 32.

Murray H series installation torque: 30 to 40 in-lb.



Sources: Breeze (NORMA Group) and Murray Corporation catalogs and spec sheets.